


Heavy Duty T-Bolt Clamps

Features:

- can be applied with a standard 1/2" socket wrench.
- 7/8" wide, .040" thick, 300 series stainless steel band
- style HTBC carbon steel bolt, torque rating: 150 in/lbs
- style HSTBC 300 series stainless steel bolt, torque rating: 150 in/lbs
- not for use with pneumatic tools 

Hose OD		style HTBC	style HSTBC
from	to	Part #	Part #
2.125"	2.4375"	<b>HTBC238</b>	<b>HSTBC238</b>
2.250"	2.5625"	<b>HTBC250</b>	<b>HSTBC250</b>
2.750"	3.0625"	<b>HTBC300</b>	<b>HSTBC300</b>
3.250"	3.5625"	<b>HTBC350</b>	<b>HSTBC350</b>
3.750"	4.0625"	<b>HTBC400</b>	<b>HSTBC400</b>
4.250"	4.5625"	<b>HTBC450</b>	<b>HSTBC450</b>
4.750"	5.0625"	<b>HTBC500</b>	<b>HSTBC500</b>
5.250"	5.5625"	<b>HTBC550</b>	<b>HSTBC550</b>
5.750"	6.0625"	<b>HTBC600</b>	<b>HSTBC600</b>
6.250"	6.5625"	<b>HTBC650</b>	<b>HSTBC650</b>
6.750"	7.0625"	<b>HTBC700</b>	<b>HSTBC700</b>
7.250"	7.5625"	<b>HTBC750</b>	<b>HSTBC750</b>
7.750"	8.0625"	<b>HTBC800</b>	<b>HSTBC800</b>
8.266"	8.562"	---	<b>HSTBC850</b>
8.646"	8.942"	---	<b>HSTBC888</b>
8.766"	9.062"	---	<b>HSTBC900</b>
9.266"	9.562"	---	<b>HSTBC950</b>
9.766"	10.062"	---	<b>HSTBC1000</b>
10.646"	10.942"	---	<b>HSTBC1088</b>
12.646"	12.942"	---	<b>HSTBC1288</b>



style HTBC



style HSTBC

Clamps

E