

Dixon™ 3-Way Ball Valves

Features:

- Valve will feed three smaller attack lines from one large diameter supply line. The three 2½" outlets are gated ball valves resulting in a safe controlled flow of water.
- equipped with an adjustable relief valve or can be capped off if a relief is not needed
- comes standard with a carrying handle
- maximum operating pressure: **280 PSI** at 70°F (21°C), without relief valve
- water way: inlet side - 4½" maximum, 3 outlets - 2½" maximum
- material: *high strength aluminum alloy, 356-T6*
- finish anodized throughout - minimum thickness 0.001"
- relief valve - double spring, cartridge type, adjustable from 50 to 200 PSI
- available with Storz fittings, male or female threads

Inlet Storz	(3) Outlets	Part #	Price	Length	Width	Height
4"	2½" Male	MSBVR3-425F	\$3060.60	16¼"	17"	11"
5"	2½" Male	MSBVR3-525F	3088.65	16¼"	17"	11"
6"	2½" Male	MSBVR3-625F	3342.95	16¼"	17"	11"
4"	2½" Female	FSBVR3-425F	3150.00	16¼"	17"	11"
5"	2½" Female	FSBVR3-525F	3150.00	16¼"	17"	11"
6"	2½" Female	FSBVR3-625F	3150.00	16¼"	17"	11"

- all measurements include handles



Dixon™ Jumbo Ball Valves

Features:

- Valve feeds multiple large diameter lines with one large diameter line. Two large gated outlets help control the flow of water and provide easy shutdown.
- equipped with a relief valve
- available with Storz fittings or threaded combinations
- up to **280 PSI** working pressure without relief valve at 70°F (21°C)
- water way: inlet side - 4½" maximum, 2 outlets - 2½" maximum
- material: *high strength aluminum alloy, 356-T6*
- finish anodized throughout - minimum thickness 0.001"
- relief valve - double spring, cartridge type, adjustable from 50 to 200 PSI

Inlet Storz	(2) Outlets Storz	Part #	Price	Length	Width	Height
4"	4"	SJBV440	\$7443.20	19½"	18"	11"
5"	4"	SJBV540	6999.70	19½"	18"	11"
5"	5"	SJBV550	7106.55	19½"	18"	11"



Dixon™ 5-Way Manifolds

Features:

- can be used to supply multiple attack lines with one large diameter line
- compact unit contains one large gated outlet, four 2½" gated outlets, pressure gauge, adjustable relief valve, and carrying handle built into the body
- maximum operating pressure: **280 PSI** at 70°F (21°C), without relief valve
- water way: inlet side - 4½" maximum, 1 outlet - 4½" maximum, 4 outlets - 2½" maximum
- finish anodized throughout: minimum thickness 0.001"
- pressure gauge: glycerine filled, PSI/KPA readings
- relief valve: double spring, cartridge type, adjustable from 50 to 200 PSI
- available with Storz fittings, male or female threads

Inlet Storz	(1) Outlet Storz	(4) Outlets Gated	Alum. Alloy, 356-T6 Part #	Price	Length	Width	Height
4"	4"	2½"	MSMG425F	\$6478.10	21"	25"	12½"
5"	5"	2½"	MSMG525F	6419.30	21"	25"	12½"
6"	6"	2½"	MSMG625F	6928.00	21"	25"	12½"

- all measurements include handles

