

Dixon® Boss LPS Frac Fittings

Male with Nut



3" and 4"




6" and 8"



HUSM500SW-1



HUSF500SW



| Size | Figure | Part # |
|------|--------|--------------------------|
| 2" | 200 | HUM200200CS ¹ |
| | 206 | HUM206200CS ² |
| 3" | 100 | HUM100300CS ¹ |
| | 200 | HUM200300CS ¹ |
| 3" | 206 | HUM206300CS ² |
| | 100 | HUM100400CS ¹ |
| 4" | 200 | HUM200400CS ¹ |
| | 206 | HUM206400CS ² |
| 6" | 100 | HUM100600CS ¹ |
| | 200 | HUM200600CS ¹ |
| 6" | 206 | HUM206600CS ² |
| | 100 | HUM100800CS ¹ |
| 8" | 200 | HUM200800CS ¹ |
| | 206 | HUM206800CS ² |

¹ Includes nut

² Includes nut and O-ring

Suction Service Fittings

| Size | Figure | Description | Forged Steel Part # |
|------|--------|---|---------------------|
| 5" | 50 | socket weld x suction male hammer union (includes O-ring, no nut) | HUSM500SW-1 |
| | | socket weld x suction female hammer union | HUSF500SW |
| 5" | N/A | split nut, suction and discharge, black | HUS500RN |

Dixon Frac Fitting O-rings

| Size | Figure | Nitrile Rubber Part # |
|------|--------|-----------------------|
| 3" | 206 | O238BU |
| 4" | 206 | O347BU |
| 6" | 206 | O440BU |
| 8" | 206 | O447BU |

King Crimp® Style Short Frac Ferrules

Features

- Schedule 40 plated carbon steel to ASTM standards
- Consult Dixon for additional ferrule sizes



| Hose I.D. | Hose O.D. | | Ferrule Wall Thickness | Ferrule I.D. | Ferrule Overall Length | Carbon Steel Part # |
|-----------|-----------|----------|------------------------|--------------|------------------------|---------------------|
| | From | To | | | | |
| 8" | 8-29/64" | 8-36/64" | .120" | 8.625" | 4.25" | CFS800-1CS |
| | 8-37/64" | 8-44/64" | .120" | 8.750" | 4.25" | CFS800-2CS |
| | 8-45/64" | 8-52/64" | .120" | 8.875" | 4.25" | CFS800-3CS |
| | 8-53/64" | 8-60/64" | .120" | 9.000" | 4.25" | CFS800-4CS |
| | 8-61/64" | 9-4/64" | .120" | 9.125" | 4.25" | CFS800-5CS |
| | 9-5/64" | 9-12/64" | .120" | 9.250" | 4.25" | CFS800-6CS |
| | 9-13/64" | 9-20/64" | .120" | 9.375" | 4.25" | CFS800-7CS |
| | 9-21/64" | 9-28/64" | .120" | 9.500" | 4.25" | CFS800-8CS |